



THERMOSTATIC HEAD WITH LIQUID SENSOR

TECHNICAL SPECIFICATIONS

CONNECTION:	M 30X1.5 mm
TEMPERATURE RANGE IN COMBINATION WITH THE VALVE BODIES:	5÷110 °C
MAX WORKING PRESSURE IN COMBINATION WITH THE VALVE BODIES:	10 bar
MAXIMUM DIFFERENTIAL PRESSURE IN THE VALVE:	1,4 bar (1/2") - 0,7 bar (3/4")
DECLARED HYSTERESIS:	0,4 K
INFLUENCE OF THE DECLARED DIFFERENTIAL:	0,55 K
INFLUENCE OF THE DECLARED WATER TEMPERATURE:	1,2 K
DECLARED RESPONSE TIME:	26 min



ADJUSTING TEMPERATURE

THE CORRECT ADJUSTMENT POSITION FOR THE THERMOSTATIC HEADS IS OBTAINED BY REFERRING TO THE FOLLOWING TABLE, WHICH MATCHES THE NUMBERING ON THE KNOB TO THE CORRESPONDING ROOM TEMPERATURES.

Position	*	1	2	3	4	5	* *
Mixing adjusted [°C]	8	10	15	20	25	30	32

OVERALL DIMENSIONS

∅	A
49	80

